BL 20 JC ATEX Z22



 \vdash

 \triangleleft

TECHNICAL DATA

	Units	BL 20 JC Z22
Suction type		Brushless motor
Power	kW	1,1 – 1,5
Voltage Frequency	V Hz	230 50/60
Maximum vacuum Maximum air flow Inlet Noise level – (EN ISO 3744) Bin capacity Dimensions Height	mBar m³/h Ø mm dB(A) Lt mm mm	230 220 50 72 20 516 X 545 1050
Weight Primary filter Type Surface area Diameter (Class EN 60335-2-69) Media Filter cleaning Absolute filter - Optional Surface area (Class - EN 1822) Media	Kg cm² mm cm²	38 Cartridge 34.000 305 M Antistatic Polyester Jet Clean® 22.000 H14 Fiberglass





Depureco Industrial Vacuums | Corso Europa, 609 -10088 Volpiano (TO) ITALY | T. +39 011.98.59.117 | depureco@depureco.com | www.depureco.com

BL 20 JC ATEX Z22





SUCTION UNIT

The suction unit is a powerful brushless motor, which is suitable to work in continuous mode. There are two filters on the motor head: one to protect the motor and the other positioned on the air outlet. The exhaust air is totally carbon free.



ANTISTATIC M CLASS CARTRIDGE

The filtration is guaranteed by an antistatic polyester cartridge filter. The cartridge is made to keep a huge filter surface in a compact space. In this way the air can pass through also when the filter is dirty. The cartridge is in M Class (BIA | En 60335-2-69) certified. It means that all particles till 1 micron are stopped by the filter so as to protect the turbine and the operator around the vacuum cleaner.



JetClean[®] FILTER CLEANING SYSTEM

The vacuum cleaner is equipped with a new filter cleaning system named JetClean[®] designed by Depureco. Thanks to the different pressure between the outside and the inside of the vacuum cleaner, the system generates a jet flow through the cartridge, detaching the dust from the filter surface. It is a fast and efficient way to keep the filter clean during the work, without stopping the motor.



COLLECTION BIN

The collected material is stocked inside a sturdy stainless steel container. Behind the vacuum cleaner there is a metal handle that permits to drop down the bin. The bin can be easily moved away because it is equipped with 4 pivoting industrial wheels. Each wheel is located on a reinforced support to guarantee the best stability during the movement, also when the container is full.

AVAILABLE OPTIONAL HEPA 14 | Absolute filter (EN 1822-5)

CE

 \times

ш